



Fabric and Quilt by Susan Cousineau



32.5" X 46"

## FABRIC REQUIREMENTS & CUTTING GUIDE

Finished Size: 32.5" X 46"

### Three Piece Blocks:

- Two 7-¼" X 14" pieces: 9700 0146
- One 7-¼" X 14" piece: 9700 0120
- Three 7-¼" X 7-¼" squares: 9702 0124
- One 7-¼" X 7-¼" square: 9703 0154
- One 7-¼" X 7-¼" square: 9701 0126
- One 7-¼" X 7-¼" square: 9703 0113

### Nine Patch Blocks:

- Three 5" X 5" squares: 9705 0128
  - Three 5" X 5" squares: 9701 0114
  - Three 5" X 5" squares: 9668 0125
  - Three 5" X 5" squares: 9701 0126
  - Three 5" X 5" squares: 9668 0113
  - Three 5" X 5" squares: 9704 0113
  - Three 5" X 5" squares: 9705 0147
  - Three 5" X 5" squares: 9668 0154
  - Three 5" X 5" squares: 9704 0142
- Optional if adding appliqued strips onto teal dot squares 9668 0154: three 1-½" X 5" pieces of the white, orange and green floral stripe section cut from 9702 0124

Borders: Four 3" strips (cut along width of fabric): 9668 0113

Back and Casing/Hanging Sleeve: 1-½ yards

Binding: ½ yard (five 2-½" wide strips) : 9701 0114

### Other Supplies:

- Cotton batting (1-3/8 yards/45" wide)
- Optional if adding appliqued strips onto teal dot squares 9668 0154: Lightweight paper-backed fusible webbing

**Instructions:** Note — All seam allowances are ¼".

1. Cut the fabric pieces as listed in the Cutting Guide.
2. Optional: Iron fusible webbing paper side up onto wrong side of stripe fabric (9702 0124). Cut out three 1-½" x 5" pieces of the white, orange and green floral stripe section from the fused fabric. Applique strips onto the teal squares as shown in the photo.
2. Using a ¼" seam allowance, refer to diagram to sew the three NINE PATCH BLOCKS and the three THREE PIECE BLOCKS together. Press seams as you sew each row together.
3. Using a ¼" seam allowance, refer to diagram to piece the six blocks together to form three rows. Press seams. Sew the three rows together.
4. Sew the side borders first. Press and trim. Sew the borders to the top and bottom. Press and trim.
5. Cut the backing fabric and batting several inches larger than the finished size of the quilt top.
6. Baste the batting in between the top and bottom layers of the quilt with the wrong sides of the quilt top and backing facing together.
7. Pin the three layers together then stitch-in-the-ditch along the seams (or quilt as desired).
8. Trim the batting and backing fabric even with the edges of the quilt top.
9. Bind quilt using your preferred binding technique. Add rod casing or hanging sleeve if desired.